

Designed to impress, the FingerTec i-Kiosk 100 is the premier fingerprint multimedia time attendance & access control system, stylishly crafted to fulfill the rising market demand for an ultra modern clocking system. The stunning FingerTec i-Kiosk presents color TFT high-definition graphical presentation for a beautiful display of icons and photos.

This product works effectively as a standalone unit complete with USB flask disk port, suitable for remote network application. It also performs excellently in a networking environment; offering multi-group network communication including TCP/IP protocol, enabling real-time data transfer for prompt and straightforward data management.

Multitasking FingerTec i-Kiosk 100 is offering various identification methods such as card and password, on top of fingerprint identification. It also enhances time and attendance functions by having work code and individual record access features.

In addition, FingerTec i-Kiosk 100 is furnished with T9 input method, short messaging, screen saver and i-Kiosk theme to add versatility to the standard time attendance and access control machine.







### TIME ATTENDANCE

- Eliminates "buddy-punching" incidents
- Collects clocking data systematically
- Manages data quickly and effective via software
- Provides ease of use with combinations of fingerprint, password and RFID / MIFARE / HID card

## ACCESS CONTROL

- Curbs unauthorized access via keyless device
- Monitors staff's movement at any time
- Controls staff's accessibility via time zone settings
- Provides extra security with combinations of fingerprint, password and RFID
- Integrates with door lock system easily (DC12V 3A EM Output)

# FEATURES & BENEFITS

- **MULTIMEDIA** Workcodes are available to allow user to input clocking reasons
- Short message display onscreen to broadcast company information to users
- · Private message short display intended for particular users
- 65k color TFT screen display for vivid color and presentation
- · Local language greetings and display available

#### CONNECTIVITY

- TCP/IP, RS232 and RS485 connections
- Multi-readers powered by software TCMS V2
- USB port available to ease data transfer

## **WEB LINK**



• http://info.fingertec.com/ikiosk100-1



Quick Start Guide

• http://info.fingertec.com/ikiosk100-2



Installation Guide

• http://info.fingertec.com/ikiosk100-3



? User Guide

• http://info.fingertec.com/ikiosk100-4



• http://info.fingertec.com/ikiosk100-5



Technical Tips

• http://info.fingertec.com/ikiosk100-6



## **Packaging**

Dimension (mm): 240(L) x 90(W) x 225(H) : 2.7kg (with AdapTec AC) 1.5kg (without AdapTec AC)



## **LAYOUT PLAN**





|  | SPECIFICATIONS  |
|--|---|
| MODEL                                  | i-Kiosk 100   |
| SURFACE FINISHING                      | Acrylonitrile Butadiene Styrene (ABS)   |
| TYPE OF SCANNER                        | Optical   |
| PRODUCT DIMENSION (L X W X H), mm      | 166 x 60 x 178  |
| STORAGE                                |   |
| Fingerprint templates                  | 12,000  |
| Transaction                            | 200,000   |
| ENROLLMENT & VERIFICATION              |   |
| Methods                                | Fingerprint (1:1, 1:N), Password & Card   |
| Recommended fingerprint per user ID    | 2   |
| Fingerprint placement                  | Any angle   |
| Verification time (sec)                | < 1   |
| • FAR (%)                              | < 0.0001  |
| • FRR (%)                              | < 1   |
| CARD TECHNOLOGY                        |   |
| • RFID: 64-bit, 125kHz                 | Yes   |
| • MIFARE: MFIS50/S70, 13.56MHz         | Made to order   |
| • HID: HID 1325, 26-bit, 125kHz        | Made to order   |
| COMMUNICATIONS                         |   |
| Method                                 | TCP/IP, RS232, RS485, USB flash disk (Optional WiFi)  |
| Baud rates                             | 9600, 19200, 38400, 57600, 115200   |
| Wiegand                                | 26-bit input/output   |
| OPERATING ENVIRONMENT                  |   |
| Temperature (°C)                       | 0 ~ 45  |
| • Humidity (%)                         | 20 ~ 80   |
| Power input                            | DC12V 3A  |
| TIME ATTENDANCE                        |   |
| • Siren                                | Built- in (Optional- External)  |
| Work codes                             | Yes   |
| MULTIMEDIA                             |   |
| • Voice                                | Yes   |
| • Display                              | 3.5" 65k color TFT screen   |
| Short messaging                        | Yes   |
| ACCESS CONTROL                         |   |
| EM lock driving output                 | DC12V 3A / Relay output   |
| Alarm output                           | NO / NC   |
| Antipassback                           | Yes   |
| VOICE /<br>DISPLAY LANGUAGE (TERMINAL) | English (Standard) / (Upon Request - Arabic / Indonesian / Spanish / Turkish /<br>Thai / Polish / Korea / Romanian / Portuguese / Dutch / Chinese / French /<br>Slovenia/ Russian/ Greek / Hebrew / Persian / Italian / Vietnamese / Czech / Bulgarian) |
| SOFTWARE LANGUAGE                      | English, Arabic, Indonesian, Spanish, Chinese, Thai, Vietnamese,<br>French, Persian, Italian, Russian, Malay, Portuguese, German, Turkish   |



